Process and Conveyor Belts

Technical datasheet

Food Grade (FG)

Anti-static (AS)

PTFE 100-06 Fibreglass S ST FG

yes

no

Article code: PPTS000003

| General information | | |
|----------------------|---------------|--|
| Product group | Peak Products | |
| | | |
| Belt construction | | |
| Fabric tension layer | Fibreglass | |
| Color | beige | |
| | | |
| Characteristics | | |

According: yes

| Technical data | | | | |
|-----------------------|------------|---------|--------------|--------------------------|
| Belt thickness | | | 0.15 mm | 0.01 in. |
| Weight | | | 0.305 kg/m² | 0.06 lbs/ft ² |
| PTFE content | | | 65 % | |
| Operating temperature | continuous | from/to | -73 / 260 °C | -99.4 / 500 °F |
| | short | from/to | -73 / 270 °C | -99.4 / 518 °F |
| Belt length | maximum | | 100000 mm | 3937.01 in. |
| Belt width | standard | | 1000 mm | 39.37 in. |
| | maximum | | 1000 mm | 39.37 in. |

| Fabrication | |
|---------------------------|---------------|
| Recommended splice method | Peak Products |

Additional information

The information applies at approx. 20 °C (68 °F). Keep the belt tension to a practical working minimum for maximum belt and machine life. Store loose and wrapped in plastic. The allowable product temperature may vary. Consult our specialists is case of questions or remarks.