Process and Conveyor Belts

Technical datasheet

NR EZP 10/1 0+42 red

Article code: ZLNR560210

General information

Product group Ziplink

 Industry segment
 Paper & print; Tyre

 Indication of use
 Slider bed, Rollers, Flat

Belt construction				
Tension layer	Ziplink fabric, flexible			
Number of plies	1			
Top side	material NR, NR			
	finish smooth			
	color red			
Bottom side	material Mesh, polyester			
	finish bare			
	color black			

Characteristics

Food Grade (FG) no

Technical data				
Hardness	according to ISO 868	top side	40A Shore	
Force at 1% elongation	according to ISO 21181		10 N/mm	57.1 lbs/in.
Thickness	internal AB method KV.002		6.7 mm	0.26 in.
		top cover	3.18 mm	0.13 in.
Weight	internal AB method KV.004		6.88 kg/m ²	1.41 lbs/ft ²
Operating temperature	continuous	from/to	-18 / 121 °C	-0.4 / 249.8 °F
Belt width	standard		1829 mm	72.01 in.
	maximum		1829 mm	72.01 in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.