

## NR EZP 10/1 01+C37 natural CR

Article code: ZLNR560111

### General information

<b>Product group</b>	ZipLink
<b>Industry segment</b>	Wood: Furniture; Airports; Logistics: Distribution & warehousing
<b>Main product feature</b>	Cold resistant
<b>Indication of use</b>	Slider bed, Rollers

### Belt construction

<b>Tension layer</b>	Ziplink fabric, flexible
<b>Number of plies</b>	1
<b>Top side</b>	<b>material</b> NR, NR
	<b>finish</b> profile, C37 Supergrip profile
	<b>color</b> natural
<b>Bottom side</b>	<b>material</b> Mesh, polyester
	<b>finish</b> bare fabric
	<b>color</b> white

### Technical data

<b>Hardness</b>	according to ISO 868	top side	40A Shore	
<b>Force at 1% elongation</b>	according to ISO 21181		10 N/mm	57.1 lbs/in.
<b>Thickness</b>	internal AB method KV.002		6.3 mm	0.25 in.
		top cover	3.81 mm	0.15 in.
<b>Weight</b>	internal AB method KV.004		2.2 kg/m <sup>2</sup>	0.45 lbs/ft <sup>2</sup>
<b>Operating temperature</b>	continuous	from/to	-40 / 121 °C	-40 / 249.8 °F
	short	from/to	-40 / 121 °C	-40 / 249.8 °F
<b>Belt width</b>	standard		1829 mm	72.01 in.
	maximum		1829 mm	72.01 in.

### Fabrication

Ziplink belts can be endless, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.