

NR EZP 10/1 01+C52 tan CR

Article code: ZLNR560116

General information

Product group	ZipLink
Industry segment	Canning & bottling; Wood; Logistics
Main product feature	Cold resistant
Indication of use	Slider bed, Rollers

Belt construction

Tension layer	Ziplink fabric, flexible
Number of plies	1
Top side	material NR, NR finish profile, C52 Diamond impression profile color tan
Bottom side	material Mesh, polyester finish smooth color white

Characteristics

ATEX approval	ATEX 2
----------------------	--------

Technical data

Hardness	according to ISO 868	top side	45A Shore	
Force at 1% elongation	according to ISO 21181		10 N/mm	57.1 lbs/in.
Thickness	internal AB method KV.002		7.2 mm	0.28 in.
		top cover	5.33 mm	0.21 in.
Weight	internal AB method KV.004		7.3 kg/m ²	1.5 lbs/ft ²
Operating temperature	continuous	from/to	-40 / 121 °C	-40 / 249.8 °F
	short	from/to	-40 / 121 °C	-40 / 249.8 °F
Belt width	standard		1829 mm	72.01 in.
	maximum		1829 mm	72.01 in.

Fabrication

Ziplink belts can be endlessed, very easy and quick splicing without presses, fasteners or glues. Refer to the technical information for more information about splicing of Ziplink belts.